

1. Product Name and Supplier

Product Name: Wood Briquettes for Heating

Product Supplier: Verdo Renewables Ltd
 45 Macadam Way
 West Portway Industrial Estate
 Andover
 Hampshire
 SP10 3XW
 Tel: +44 1264 342000
 Fax: +44 1264 723929

2. Composition/Information on Ingredients

Ingredients

Raw Material: 100% virgin soft wood.

Additives or Binders: No additives or binders are used in the production.

Composition

Wood Briquettes are manufactured from lingo-cellulosic saw dust and wood chips by means of one or a combination of the following operations; drying, size reduction, densification, cooling and dust removal. The chemical composition of Wood Briquettes varies between species of raw material, components of the wood, soil conditions and the age of the tree. Wood Briquettes are typically manufactured from a blend of feedstock with the following compositions;

	Spruce	Pine
Cellulose	39.5	40
Hemi-cellulose	30.6	28.5
Lignin	27.5	27.5
Extractives (terpene, fatty acids, phenols)	2.1	3.5

Indicative composition in % of weight.

3. Hazardous Identification

Various species of wood produce a dust that can elicit allergic contact dermatitis in sensitised individuals. In non-sensitised individuals the dust may cause irritation in the eyes and respiratory organs.

If the Briquettes become wet or moist, a biological process is started in the material that causes the temperature to rise; this may result in self combustion.

Wood is a strong to severe explosion hazard if a dust “cloud” contacts an ignition source.

Wood heated with limited oxygen will produce CO, CO₂, and hydrocarbons which can explode if oxygen is introduced.

When storing/transporting in closed spaces with insufficient ventilation, e.g. silos or cargo holds on ships, carbon monoxide can be formed.

4. First Aid Measures

- Ingestion:** Rinse mouth thoroughly with water, do not ingest water or induce vomiting. Wood Briquettes will expand about 3 or 4 times in volume when wet. No harmful effects, if there is a discomfort seek medical advice.
- Inhalation:** Remove to fresh air or a ventilated area. If persistent irritation, severe coughing or breathing difficulties occur, seek medical advice.
- Skin Contact:** Wash with soap and water and remove contaminated clothing. If a rash or persistent irritation or dermatitis occurs, seek medical advice.
- Eye Contact:** Flush with copious amounts of water for at least 10 minutes or use an eye wash solution. If irritation persists seek medical advice.

5. Fire Fighting Measures

- Extinguishing Media:** Foam, Water, Sand, Carbon Dioxide and Nitrogen. Use inert gases to smother fires in enclosed spaces.
- Unusual Fire Hazards:** None
- Special:** Use water to wet down dust to reduce the likelihood of ignition on dispersion of dust into the air.
- Protection of Fire Fighters:** Wear self-contained breathing apparatus and full clothing, such as turnout-out gear.

6. Accidental Release Measures

Sweep or vacuum spills for recovery or disposal; avoiding creating dust conditions. Provide good ventilation where dust conditions may occur. Place recovered dust in a container for disposal.

Broken wood briquettes and wood dust on the floor present a slip and fall hazard.

7. Handling and Storage

- Handling:** Wash hands immediately after handling and before eating.
- Storage:** Store in cold, dry areas shielded from the weather. We recommend that storage spaces, where possible are well ventilated.
- Avoid contact with Oxidizing Agents and Drying Oils
- Do not allow the product to become wet, water will expand and breakdown the Briquettes into wood particles.

8. Exposure Control and Personal Protection

- Ventilation:** Provide local exhaust ventilation, other engineering controls or adequate general ventilation to keep the airborne concentrations below the respective occupational exposure limit.
- Maximum Exposure Limit:** TWA 5 mg/m³ Sen 8 hour(s) EH40 MEL (Softwood)
- Personal Protective Equipment:** Goggles and approved dust respirators may be required depending upon dust conditions.

9. Physical and Chemical Properties

- Appearance:** Light to dark coloured cylinders 7cm square. Approximately 30cm long with some wood dust.
- Odour:** Slight wood odour.

Minimum Ignition Temperature (MIT):	Briquettes; Non Applicable Dust Cloud 480°C Dust Layer 260°C
Auto Ignition Temperature:	+260°C in the presence of oxygen.
Energy Content:	Min 4.8 – 4.9 MWh/tonne, effective heat content.
Ash Content:	≤ 0.7%
Bulk Density:	≥ 600 kg/m ³
Moisture:	≤ 10%
Solubility:	Insoluble. Water will expand and breakdown the Briquettes into wood particles.

10. Stability and Reactivity

Stability:	Stable under normal conditions.
Incompatibility:	Avoid contact with oxidizing agents and drying oils. Avoid open flame; product may ignite at temperatures in excess of 260°C. Avoid contact with water; decomposition will occur.
Hazardous Decomposition Products:	Thermal-oxidative degradation of wood produces irritating and toxic fumes and gases, including carbon monoxide, terpenes and polycyclic aromatic hydrocarbons.

11. Toxicological information

Routes of Exposure

Inhalation:	Constant exposure can result in work related asthma. Inhalation of dust in high concentrations may cause irritation of the respiratory system.
Skin Contact:	Various species of wood produce a dust that can elicit allergic contact dermatitis in sensitised individuals.
Ingestion:	Harmful if swallowed, may cause some discomfort as Wood Briquettes will expand about 3 or 4 times in volume when wet.
Eye Contact:	Exposure to dust may cause an irritation.
Other:	Studies have shown no evidence of softwood dust being carcinogenic.

12. Ecological Information

Ecotoxicity:	The product is not expected to be hazardous to the environment.
---------------------	---

13. Disposal Considerations

Normal Waste:	Normal waste from wood Briquettes is not environmentally hazardous, dispose of in accordance with local regulations.
Contaminated Waste:	Contaminated products should be disposed of as hazardous waste, by a registered Waste Disposal Contractor.

14. Transport Information

This product is not classified as Dangerous Goods.

15. Regulations

This product is not covered by the Chemical (Hazards Information and Packaging for Supply) Regulations 2009 (CHIP)

Risk Phrase: R10, Flammable.
R22, Harmful if swallowed.
R37, Irritating to respiratory system.
R43, May cause sensitisation by skin contact.

Safety Phrase: S22, Do not breath dust.
S38, In case of insufficient ventilation, wear suitable respiratory equipment.

16. Other Information

When storing/transporting in closed spaces with insufficient ventilation, e.g. silos or cargo holds on ships, carbon monoxide can be formed. We advise that air samples are taken with a carbon monoxide meter prior to any personnel entering such areas.

Legal Disclaimer:

The purpose of the above information is to describe the product only in terms of Health and Safety requirements. The information given should not, therefore, be construed as guaranteeing specific properties or as specification. Customers should satisfy themselves as to the suitability and completeness of such information for their own particular use.